

Sistemas split de 4 a 8 kW

Combinaciones con Hydrobox Duo (Gen-D)



Kits Recomendados

NOMBRE KIT			ATW-P4M-T20D	ATW-P6M-T20D	ATW-P8M-T20D
Unidad exterior	Modelo		SUZ-SWM40VA	SUZ-SWM60VA	SUZ-SWM80VA
	PVR	€	1.773 €	1.990 €	2.533 €
Unidad Interior	Modelo		ERST20D-VM2D	ERST20D-VM2D	ERST20D-VM2D
	PVR	€	4.223 €	4.223 €	4.223 €
Interfaz Wifi	Modelo		MAC-567IF-E	MAC-567IF-E	MAC-567IF-E
	PVR	€	99 €	99 €	99 €
PVR Kit			6.095 €	6.312 €	6.855 €

Unidades exteriores

4,00 kW
5,60 kW



6,00 kW
6,00 kW



7,50 kW
6,30 kW



MODELO			SUZ-SWM40VA	SUZ-SWM60VA	SUZ-SWM80VA
Dimensiones	Al. x An. X Fo.	mm	880 x 840 x 330	880 x 840 x 330	880 x 840 x 330
	Peso neto	kg	54	54	54
Tuberías frigoríficas	Ø Líquido / Gas	mm	6,35 (¼") / 12,7 (½")	6,35 (¼") / 12,7 (½")	6,35 (¼") / 12,7 (½")
	L. máx / Altura máx.	m	30 / 30	30 / 30	30 / 30
Nivel sonoro	SPL (Calor/Frío)	dB	44 / 49	45 / 49	46 / 49
	PWL (Calor)	dB	58	60	62
Gas refrigerante R32 (GWP 675)	Precarga (kg / m / t CO2 Eq.)		1,2 / 10 / 0,81	1,2 / 10 / 0,81	1,2 / 10 / 0,81
	Carga máx (kg / m / t CO2 Eq.)		1,6 / 30 / 1,08	1,6 / 30 / 1,08	1,6 / 30 / 1,08
Rango de funcionamiento	Calor	°C	-20 — +24	-20 — +24	-20 — +24
	ACS	°C	-20 — +35	-20 — +35	-20 — +35
	Frío	°C	+10 — +46	+10 — +46	+10 — +46
Salida de agua	máx calor / mín frío	°C	+60 / +5	+60 / +5	+60 / +5
PVR			1.773 €	1.990 €	2.533 €

No compatibles con unidades interiores generación "C".

170L



200L



300L



Unidades interiores

MODELO			ERST17D-VM2D	ERST20D-VM2D	ERST30D-VM2ED
Dimensiones	Al. x An. X Fo.	mm	1400 x 595 x 680	1600 x 595 x 680	2050 x 595 x 680
	Peso vacío/lleño	kg	93 / 269	104 / 310	114 / 421
Nivel sonoro (PWL)		dB(A)	41	41	41
Vaso expansión	Vol. / Presión carga		12L / 0,1MPa	12L / 0,1MPa	--
Conexión tubería de agua	Circuito primario	mm	Ø28 mm	Ø28 mm	Ø28 mm
	Circuito ACS	mm	Ø22 mm	Ø22 mm	Ø22 mm
Tuberías refrig.	Ø Líquido / Gas	mm	6,35 (¼") / 12,7 (½")	6,35 (¼") / 12,7 (½")	6,35 (¼") / 12,7 (½")
Bomba	Modelo		Grundfos UPM3K 15-75 130	Grundfos UPM3K 15-75 130	Grundfos UPM3K 15-75 130
Resist. apoyo	Fase / Potencia / Corriente (PIA)		1 ~ / 2kW / 9A (PIA: 16A)	1 ~ / 2kW / 9A (PIA: 16A)	1 ~ / 2kW / 9A (PIA: 16A)
Tanque ACS	Volumen	L	170	200	300
	Material		Acero Inoxidable	Acero Inoxidable	Acero Inoxidable
PVR			4.139 €	4.223 €	4.434 €

Modelos de 170L y 300L: Consultar disponibilidad.